




EN 388:2016



DR1HPA

Also available with hangtag: PRO HYDRO

Size 8 to 11

Polybag : 10 pairs

Box : 100 pairs

Lenght 27cm (T10)

Water-repellent cowgrain leather driver glove.
Protects arteries.



EN388

Abrasion: 3/4

Cut: 1/5

Tear: 2/4

Puncture: 2/4

ISO13997 : X/F

Safety precautions:

- Before use, check the gloves for defects, holes, tears or abnormal wear.
 - Wear gloves on dry, clean hands.
- Pre-testing of gloves is recommended, the actual conditions of use may differ from those of the EC type tests.

Recommended uses:

- This glove is intended for handling dry and wet parts.
- Industrial, construction and community environments

Safety concerns:

- Dexterity level 5
- This PPE does not contain any substance at known or suspected levels that may adversely affect the health of the user.
(in standard conditions of use)

Storage and maintenance :

- Store in a dry, ventilated and dark place.
- No special maintenance
- The disposal of this glove must comply with European traceability and environmental requirements

NT PRO SAS

5b, rue des Cigognes F-68590 RORSCHWIHR

Bureau : + 33 (0)3 89 73 50 63

www.nt-pro.com – Mail: contact@nt-pro.com

Siret : 815378682 00018 – N°TVA Intracommunautaire : FR 49 815378682