




EN 388:2016



MAGIC TOUCH

Size 6 to 11

Polybag : 10 pairs

Box : 40 pairs

Lenght 27cm (T10)



Polyester/lycra glove gauge 15
Polyurethane palm coating.
EverShield® Technology
Water-repellent and breathable

EN388

Abrasion: 3/4

Cut: 1/5

Tear: 2/4

Puncture: 1/4

ISO13997 : X/F



EVERSHIELD



Safety precautions:

- Before use, check the gloves for defects, holes, tears or abnormal wear.
 - Wear gloves on dry, clean hands.
- Pre-testing of gloves is recommended,
the actual conditions of use may differ from those of the EC type tests.

Recommended uses:

- This glove is intended for handling dry parts.
- Industrial, automotive, gardening ; handling environments.

Safety concerns:

- Dexterity level 5
- This PPE does not contain any substance at known or suspected levels that may adversely affect the health of the user.
(in standard conditions of use)

Storage and maintenance :

- Store in a dry, ventilated and dark place.
- No special maintenance
- The disposal of this glove must comply with European traceability and environmental requirements

NT PRO SAS

5b, rue des Cigognes F-68590 RORSCHWIHR

Bureau :+ 33 (0)3 89 73 50 63

www.nt-pro.com – Mail: contact@nt-pro.com

Siret : 815378682 00018 – N°TVA Intracommunautaire : FR 49 815378682