Intermediary risks - Cat II labo : CIMAC 0465 EN420 / 03 + A1 - EN388 2016 - EN ISO 13997





EN 388:2016



NOVA LO30 3/4

Also available with hangtag: PRO JARDIN

**Size 8 to 10** 

Polybag: 10 pairs Box: 100 pairs Lenght 27cm (T10)



Polyester glove gauge 13 3/4 latex coating.

### **EN388**

Abrasion: 2/4
Cut: 1/5
Tear: 3/4
Puncture: 2/4
ISO13997: X/F





# Safety precautions:

•Before use, check the gloves for defects,

holes, tears or abnormal wear.

• Wear gloves on dry, clean hands.

Pre-testing of gloves is recommended,

the actual conditions of use may differ from those of the EC type tests.

## Recommended uses:

This glove is intended for handling oily and wet parts.

• Industrial, construction and community environments

# **Safety concerns:**

- Dexterity level 5
- This PPE does not contain any substance at known or suspected levels that may adversely affect the health of the user.

(in standard conditions of use)

## Storage and maintenance:

- Store in a dry, ventilated and dark place.
- No special maintenance
- The disposal of this glove must comply with European traceability and environmental requirements

#### **NT PRO SAS**

5b, rue des Cigognes F-68590 RORSCHWIHR Bureau :+ 33 (0)3 89 73 50 63

www.nt-pro.com – Mail: contact@nt-pro.com Siret: 815378682 00018 – N°TVA Intracommunautaire: FR 49 815378682