





## NOVA L051

Also available with hangtag : L051 C

EN 388:2016



EN 511



Size 8 to 11

Polybag : 10 pairs

Box : 100 pairs

Lenght 27cm (T10)



Polyester glove, acrylic lining, gauge 10  
Latex coating in the palm

### EN388

Abrasion:	3/4
Cut:	1/5
Tear:	4/4
Puncture:	2/4
ISO13997 :	X/F

### EN511

Convective cold :	1/4
Contact cold :	1/4
Waterproofing :	X/4



### Safety precautions:

- Before use, check the gloves for defects, holes, tears or abnormal wear.
  - Wear gloves on dry, clean hands.
- Pre-testing of gloves is recommended, the actual conditions of use may differ from those of the EC type tests.

### Recommended uses:

- This glove is intended for handling sharp and wet parts in cold weather.
- Industrial, construction and community environments

### Safety concerns:

- Dexterity level 5
- This PPE does not contain any substance at known or suspected levels that may adversely affect the health of the user.  
(in standard conditions of use)

### Storage and maintenance :

- Store in a dry, ventilated and dark place.
- No special maintenance
- The disposal of this glove must comply with European traceability and environmental requirements

### NT PRO SAS

5b, rue des Cigognes F-68590 RORSCHWIHR  
Bureau : + 33 (0)3 89 73 50 63

[www.nt-pro.com](http://www.nt-pro.com) – Mail: [contact@nt-pro.com](mailto:contact@nt-pro.com)

Siret : 815378682 00018 – N°TVA Intracommunautaire : FR 49 815378682