




EN 388:2016



## NOVA L056

*Also available with hangtag : PRO  
ETANCHE*

Size 8 to 10

Polybag : 10 pairs

Box : 100 pairs

Lenght 27cm (T10)



Hardened glove on polyamide liner gauge 13  
Double coated latex/latex foam.

### EN388

Abrasion:	2/4
Cut:	1/5
Tear:	3/4
Puncture:	1/4
ISO13997 :	X/F



### Safety precautions:

- Before use, check the gloves for defects, holes, tears or abnormal wear.
  - Wear gloves on dry, clean hands.
- Pre-testing of gloves is recommended,  
the actual conditions of use may differ from those of the EC type tests.

### Recommended uses:

This glove is intended for handling oily and wet parts.

- Industrial, construction and community environments

### Safety concerns:

- Dexterity level 5
- This PPE does not contain any substance at known or suspected levels that may adversely affect the health of the user.  
(in standard conditions of use)

### Storage and maintenance :

- Store in a dry, ventilated and dark place.
- No special maintenance
- The disposal of this glove must comply with European traceability and environmental requirements

### NT PRO SAS

5b, rue des Cigognes F-68590 RORSCHWIHR

Bureau :+ 33 (0)3 89 73 50 63

[www.nt-pro.com](http://www.nt-pro.com) – Mail: [contact@nt-pro.com](mailto:contact@nt-pro.com)

Siret : 815378682 00018 – N°TVA Intracommunautaire : FR 49 815378682