




EN 388:2016



3121X

## NOVA PU001

*Polybag with hole also available: PRO PRECISION*

Size 6 to 11

Polybag : 12 pairs

Box : 120 pairs

Lenght 27cm (T10)

Grey polyester knitted glove gauge 13  
Grey polyurethane palm coating



### EN388

Abrasion: 3/4

Cut: 1/5

Tear: 2/4

Puncture: 1/4

ISO13997 : X/F



### Safety precautions:

- Before use, check the gloves for defects, holes, tears or abnormal wear.
  - Wear gloves on dry, clean hands.
- Pre-testing of gloves is recommended, the actual conditions of use may differ from those of the EC type tests.

### Recommended uses:

- This glove is intended for handling dry or slightly greasy parts.
- Industrial, construction and community environments

### Safety concerns:

- Dexterity level 5
- This PPE does not contain any substance at known or suspected levels that may adversely affect the health of the user.  
(in standard conditions of use)

### Storage and maintenance :

- Store in a dry, ventilated and dark place.
- No special maintenance
- The disposal of this glove must comply with European traceability and environmental requirements

### NT PRO SAS

5b, rue des Cigognes F-68590 RORSCHWIHR

Bureau :+ 33 (0)3 89 73 50 63

[www.nt-pro.com](http://www.nt-pro.com) – Mail: [contact@nt-pro.com](mailto:contact@nt-pro.com)

Siret : 815378682 00018 – N°TVA Intracommunautaire : FR 49 815378682