




EN 388:2016



**PRO OIL CUT 3/4**

Size 6 to 11

Polybag : 10 pairs

Box : 100 pairs

Lenght 27cm (T10)



HPPE glove + 13 gauge stainless steel wire  
¾ nitrile coating and foam nitrile palm

**EN388**

Abrasion: 4/4  
Cut: X/5  
Tear: 4/4  
Puncture: 3/4  
ISO13997 : D/F

**TDM F  
34,3N**

**SOFT/NOX®**



**Safety precautions:**

- Before use, check the gloves for defects, holes, tears or abnormal wear.
  - Wear gloves on dry, clean hands.
- Pre-testing of gloves is recommended, the actual conditions of use may differ from those of the EC type tests.

**Recommended uses:**

- This glove is intended for handling dry, wet and oily cutting parts.
- Industrial, construction and community environments

**Safety concerns:**

- Dexterity level 5
- This PPE does not contain any substance at known or suspected levels that may adversely affect the health of the user.  
(in standard conditions of use)

**Storage and maintenance :**

- Store in a dry, ventilated and dark place.
- No special maintenance
- The disposal of this glove must comply with European traceability and environmental requirements

**NT PRO SAS**

5b, rue des Cigognes F-68590 RORSCHWIHR

Bureau :+ 33 (0)3 89 73 50 63

[www.nt-pro.com](http://www.nt-pro.com) – Mail: [contact@nt-pro.com](mailto:contact@nt-pro.com)

Siret : 815378682 00018 – N°TVA Intracommunautaire : FR 49 815378682