


Intermediary risks - Cat II labo : CTC-0075

EN420 / 03 + A1 - EN388 2016

EN407 2004 – EN12477 TYPE B



EN 388:2016



EN 407



S012R20

Size 9 to 11

Polybag : 10 pairs

Box : 100 pairs

Lenght 42cm (T10)



Cowgrain leather welder's glove with crust back.
20cm natural crust cuff.

Aramid seams

EN388

Abrasion: 3/4
Cut: 1/5
Tear: 2/4
Puncture: 2/4
ISO13997 : X/F

EN407

Fire behavior : 4/4
Contact heat : 1/4
Convective heat : 2/4
Radiant heat : 2/4
Liquid metal spray : 4/4

Safety precautions:

- Before use, check the gloves for defects, holes, tears or abnormal wear.
 - Wear gloves on dry, clean hands.
- Pre-testing of gloves is recommended, the actual conditions of use may differ from those of the EC type tests.

Recommended uses:

- This glove is intended for handling dry and high temperature parts.
- Industrial, construction and community environments

Safety concerns:

- Dexterity level 5
- This PPE does not contain any substance at known or suspected levels that may adversely affect the health of the user.
(in standard conditions of use)

Storage and maintenance :

- Store in a dry, ventilated and dark place.
- No special maintenance
- The disposal of this glove must comply with European traceability and environmental requirements

NT PRO SAS

5b, rue des Cigognes F-68590 RORSCHWIHR

Bureau : + 33 (0)3 89 73 50 63

www.nt-pro.com – Mail: contact@nt-pro.com

Siret : 815378682 00018 – N°TVA Intracommunautaire : FR 49 815378682