




SO2DC15 RED

EN 388:2016



EN 407



Size 9 to 11

Ploybag : 10 pairs

Box : 100 pairs

Lenght 42cm (T10)



Cowsplit leather welder's glove.

Cotton lining

15cm cuff.

Aramid seams

EN388

Abrasion: 3/4

Cut: 1/5

Tear: 3/4

Puncture: 3/4

ISO13997 : X/F

EN407

Fire behavior : 4/4

Contact heat : 1/4 & 250°C for 11s

Convective heat : 3/4

Radiant heat : 1/4

Liquid metal spray : 4/4

Safety precautions:

- Before use, check the gloves for defects, holes, tears or abnormal wear.

- Wear gloves on dry, clean hands.

Pre-testing of gloves is recommended, the actual conditions of use may differ from those of the EC type tests.

Recommended uses:

- This glove is intended for handling dry and high temperature parts.

- Industrial, construction and community environments

Safety concerns:

- Dexterity level 5

- This PPE does not contain any substance at known or suspected levels that may adversely affect the health of the user.

(in standard conditions of use)

Storage and maintenance :

- Store in a dry, ventilated and dark place.

- No special maintenance

- The disposal of this glove must comply with European traceability and environmental requirements

NT PRO SAS

5b, rue des Cigognes F-68590 RORSCHWIHR

Bureau :+ 33 (0)3 89 73 50 63

www.nt-pro.com – Mail: contact@nt-pro.com

Siret : 815378682 00018 – N°TVA Intracommunautaire : FR 49 815378682